

O₂ - Gas Sensors containing acid electrolyte



:: I - PRODUCT IDENTIFICATION ::

Product: Electrochemical Oxygen Sensor, Industrial cells with acid electrolyte

Manufacturer: IT Dr. Gambert GmbH

Address: Hinter dem Chor 21
23966 Wismar
Germany

Phone: +49 (0) 3841 22 00 50
Fax: +49 (0) 3841 22 00 546

Technical Support: itg@itg-wismar.de
Environment, Health, Safety: winfried.kaemtner@itg-wismar.de

Date Prepared: 3. Febr. 2002

:: II - HAZARDOUS INGREDIENTS/COMPOSITION ::

Material or Component	C.A.S. #	Quantity	OSHA PEL	ACGIH
Lead (Pb)	7439-92-1	10-13 gms	0.05 mg/m ³	0.15 mg/m ³
Acetic acid (CH ₃ COOH)	64-19-7	2.5 ml	25 mg/m ³ (8-hour TWA)	25 mg/m ³ (8-hour TWA)
Phosphoric acid (H ₃ PO ₄)	7664-38-2	1.5 ml	1 mg/m ³	1 mg/m ³ (8-hour TWA)

:: III - HEALTH HAZARD DATA ::

Routes of Entry:	Inhalation: Highly unlikely. Ingestion: May be fatal if swallowed. May contain soluble lead salts. Skin: The electrolyte contains acetic or phosphoric acid and is corrosive; skin contact may cause irritation or severe chemical burns. Eyes: The electrolyte contains acetic or phosphoric acid and is corrosive; eye contact may cause irritation or severe chemicals burns.
Acute Effects:	The electrolyte is harmful if swallowed, inhaled or absorbed through the skin. It is destructive to tissue of the mucous membranes, stomach, mouth, upper respiratory tract, eyes and skin.
Chronic Effects:	Prolonged exposure with the electrolyte has a destructive effect on tissue. Incorporation of lead salts may cause diseases of the blood and blood forming organs, kidneys and liver, damage to the reproductive systems and decrease in fertility in men and women, and damage to the fetus of a pregnant woman. Chronic exposure from the lead contained in this product is extremely unlikely.
Signs and Symptoms of Exposure:	Contact of electrolyte with skin or eyes will cause a burning sensation. Other symptoms of exposure to lead include loss of sleep, loss of appetite, metallic taste and fatigue. For additional exposure information refer to 29 CFR 1910.1025, Appendix A – Substance Data Sheet for Occupational Exposure to Lead.
Carcinogenicity:	As the cell is used, lead acetate or lead phosphate is formed in the electrolyte. Lead is classified by the IARC as a class 2B carcinogen (possibly carcinogenic to humans).
OSHA:	Where airborne lead exposures exceed the OSHA action level, refer to OSHA Lead Standard 1910.1025.
NTP:	n.a.
Medical Conditions Generally Aggravated by Exposure:	Lead exposure may aggravate disease of the blood and blood forming organs, hypertension, kidneys, nervous and possibly reproductive systems. Those with pre-existing skin disorders or eye problems may be more susceptible to the effects of the electrolyte.

:: IV - EMERGENCY FIRST AID PROCEDURES ::

In case of contact with the skin or eyes, immediately flush with plenty of water for at least 15 minutes and remove all contaminated clothing. Get medical attention immediately.

If ingested, give large amounts of water and DO NOT INDUCE VOMITING. Obtain medical attention immediately.

If inhaled, remove to fresh air and obtain medical attention immediately.

:: V - FIRE AND EXPLOSION HAZARD DATA ::

Flash Point: n.a.	Flammable Limits: n.a.	LEL: n.a.	UEL: n.a.
Extinguishing Media:	Use extinguishing media appropriate to surrounding fire conditions. No specific agents recommended.		
Special Fire Fighting Equipment:	Wear NIOSH/OSHA approved self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.		
Unusual Fire and Explosion Hazards:	n.a.		
Fire Protection Classification:	B1 (DIN 4102)		

:: VI - CLEANUP PROCEDURES ::

Wipe down the area several times with a wet paper towel. Use a fresh towel each time. Contaminated paper towels are considered hazardous waste.

:: VII - PRECAUTIONS FOR SAFE HANDLING AND USE ::

Note: The oxygen sensors are sealed and under normal circumstances the contents of the sensors do not present a health hazard. The following information is given as a guide in the event that a cell leaks.

Protective Measures During Cell Replacement:	Before installing the sensor cell, check the sensor cell for leakage. If the sensor cell leaks, do not use it. If there is liquid around the cell while in the instrument, wear eye and hand protection.
---	--

:: VIII- EXPOSURE CONTROLS/PERSONAL PROTECTION ::

Eye Protection:	Chemical splash goggles
Hand Protection:	Rubber gloves
Other Protective Clothing:	Apron, face shield
Ventilation:	n.a.

:: IX - PHYSICAL/CHEMICAL CHARACTERISTICS ::

Material or Component	Boiling Point (°C)	Specific Gravity	Vapor Pressure	Melting Point (°C)	Density	Evap. Rate	Solubility in Water	Odor/Appearance Physical State
Lead	1744	11.34	n.a.	328	n.a.	n.a.	Insoluble	Solid, silver, grey, odourless
Acetic Acid (10 % in Water)	n.a.	1.01	n.a.	n.a.	n.a.	n.a.	Complete	Clear, colorless liquid with vinegar odor
Phosphoric Acid (85 % in Water)	n.a.	1.71	6 mm Hg	-57 (at 20°C)	n.a.	n.a.	Complete	Clear, colorless liquid without odor

:: X - STABILITY AND REACTIVITY ::

Stability:	Stable
Incompatibilities:	Non-precious metals, copper, Bases
Hazardous Decomposition:	Toxic fumes
Hazardous Polymerization	Will not occur.

:: XI - TOXICOLOGICAL INFORMATION ::

Toxicity to Animals:	Acute oral toxicity (LD50) for acetic acid and phosphoric acid: n.a. Acute oral toxicity (LD50) for lead: n.a.
Mutagenicity:	Lead tested positive as a mutagen in the Ames test.

:: XII - ECOLOGICAL INFORMATION ::

Ecotoxicity:	The LC50 of lead for the daphnia magna is 3.6 mg/l, and 5.1 mg/l for the daphnia pulex.
Environmental Fate:	Lead is bioaccumulative in most aquatic life and mammals. It is highly mobile as lead dust or fume, yet forms complexes with organic material which limits its mobility.

:: XIII - DISPOSAL CONSIDERATIONS ::

Waste must be disposed of in accordance with Federal, State and Local environmental control regulations. If discarded in its purchased form, this product is hazardous by its characteristics of toxicity and corrosivity under RCRA. Must follow all State and Local regulations.

EPA Waste Number:	D008, D002
DOT Information:	Corrosive liquid, acid, inorganic, n.o.s. (lead, phosphoric acid, acetic acid), 8, UN 3266, II.

:: XIV - TRANSPORT INFORMATION ::

DOT: Regulated. Refer to Small Quantity Exceptions: 49 CFR 173.4.
IATA: Regulated. Refer to IATA Dangerous Goods in Excepted Quantities, Sec. 2.7

:: XV - REGULATORY INFORMATION ::

European Community:

Acetic acid, phosphoric acid (liquid)
R10-35 – Causes severe burns.
R42 – May cause sensitization by inhalation.
R36/37/38 – Irritating to eyes, respiratory system and skin.

US Federal Regulations:

- 1) OSHA – Hazardous by definition of Haz Com Std. 29 CFR 1910.1200
- 2) SARA TITLE III
 - Sec 302 (40 CFR Part 355):
Not applicable as to “chemical name”: CAS #, %, TPQ lbs, RQ.
 - Sec 311 & 312:
Lead: Acute/Chronic Health Hazard: Yes.
Fire/Sudden Release of Pressure Hazard, Reactivity: No.
 - Sec 313 (40 CFR Part 372):
This product contains the following toxic chemicals subject to the reporting requirements of Section 313, of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
Lead: CAS # 7439-92-1, Content 5 – 13 gms
- 3) TSCA (Toxic Substances Control Act)
Components of this product are listed on the TSCA inventory.
- 4) CERCLA Section 102(A) (40 CFR Part 302)
Hazardous Substances and Reportable Quantities
Lead: CAS # 7439-92-1, Content 10 lbs.

Canada:

Canadian Environmental Protection Act (CEPA): Phosphoric acid and acetic acid are on the Domestic Substances List (DSL) and acceptable for use under the provisions of CEPA.

WHMIS: Acetic acid, Phosphoric acid Class E: Corrosive liquid
Lead Class D-2A

:: XVI – OTHER INFORMATION ::

All chemicals may pose unknown hazards and should be used with caution. While the information contained in this Material Safety Data Sheet is believed to be correct and is offered for your information, consideration and investigation, IT Dr. Gambert GmbH assumes no responsibility for the completeness or accuracy of the information contained herein.